



AUTOMATION 2-in-1

*Incubator  
+  
Orbital Shaker*

*Up to 16  
samples*

*Fully  
Automation*





**AUTOMATION  
2-in-1**

***Consistent & stable control***

- | Speed Range: Orbit 4 mm, 300—3,000 rpm.  
(1,000 rpm and 2,500 rpm are labeled.)  
Minimum Speed: 10 rpm  
(rotation speed change step | increment value)
- | Temperature Range: 5°C - 60°C.  
(30° C, 37° C, and 44°C are labeled.)  
Temperature Control Accuracy/Uniformity:  $\pm 0.5^{\circ}\text{C}$   
Temperature Accuracy at 37°C is  $\pm 0.25^{\circ}\text{C}$
- | Heating Rate: 20° C to 60° C in less than 12 minutes.
- | Display Accuracy  $\pm 0.1^{\circ}\text{C}$
- | Time Frame: 1 second to 168 hours



### ***Carry out 1 to 16 sample tubes/vials simultaneously***

- ① Tube/Vials Capacity: 0.2 ml, 0.5 ml, 1.5 ml, 1.7 ml, 2.0 ml, 10 ml, 11 ml, 15 ml, 25 ml
- ② The device can be remotely controlled and connected.
- ③ The device can set up more than 100 protocols.
- ④ Password and login security.
- ⑤ USB port for charging and data transmission.
- ⑥ Large touch screen.
- ⑦ 100-240 V, 12 V-5 V battery, and 50—60 Hz frequency.
- ⑧ Forced Air convection for temperature control.
- ⑨ Operational temperature: 8-40°C.
- ⑩ UL/CE standard.



*For more info, contact us  
at:*

[www.royalbiotech.com](http://www.royalbiotech.com)  
[info@royalbiotech.com](mailto:info@royalbiotech.com)